



# Technical Information

---

## 1 Product Name

---

Mirro-Mastic®

## 2 Manufacturer

---

Palmer Products Corporation  
146 St. Matthews Ave.  
Louisville, KY 40207

**Phone**

800.431.6151  
502.893.3668

**Fax**

502.895.9253

**Website**

mirro-mastic.com

**E-mail**

palmer@mirro-mastic.com

## 3 Product Description

---

**Basic Use**

Mirro-Mastic® is a high quality adhesive mastic formulated for adhering acrylic and glass mirror to various substrates such as drywall, wood, glass, metal or tile.

## 4 Technical Data

---

**Appearance**

Heavy paste

**Application temperature**

59°F to 95°F (15°C to 35°C)

**Cleanup**

Mineral spirits

**Color**

Black

**Composition and materials**

Mirro-Mastic® is an asphalt base adhesive

**Coverage**

With **minimum** coverage, one 11 fl oz (325 ml) cartridge will install approximately 12 square feet (1.1 square meters) of mirror, one 29 fl oz (858 ml) cartridge will install approximately 30 square feet (2.8 square meters) of mirror, one gallon (3.785 L) will install approximately 130 square feet (12 square meters) of mirror and one 5 gallon (18.927 L) pail will install 640 square feet (60 square meters)

**Cure time**

Curing time will depend on temperature, humidity, type of substrate and amount of air that can reach the mastic

**Density**

No data available

**Flash point**

Over 160°F (71.1°C)

**Packaging**

11 fl oz (325 ml) cartridge (24 per case)  
29 fl oz (858 ml) cartridge (12 per case)  
1 gallon (3.785 L) can (4 per case)  
5 gallon (18.927 L) pail

**Shelf life**

Two years from the production date for an unopened can  
One year from the production date for an unopened cartridge

**Storage**

50°F to 85°F (10°C to 29.4°C)

**Viscosity**

No data available

**VOC content**

230 g/L

---

**WARNING:** All Palmer products must be used only for approved purposes, and must be applied only in accordance with Palmer's installation instructions. The user bears all risk of damage, injury or other loss arising out of any nonapproved use and/or improper installation of any Palmer product. If Palmer's installation instructions are not followed, in whole or part, for whatever reason, then mechanical fasteners of sufficient size and strength must immediately be used to insure safety of the installation pending prompt proper reinstallation by the product user. Any failure to properly utilize or apply any Palmer product may result in property damage, bodily injury or death. Palmer shall not be responsible for these or any other types of misuse of its products.