

# 2800

# Lowry

The Tape Specialists



## POLYPROPYLENE PACKAGING TAPE

### PRODUCT DESCRIPTION

Polypropylene Packaging Tape 2800 features a water-based acrylic sensitive adhesive, providing a strong and reliable seal for lightweight cartons. Whether you're packing items for shipping, organizing storage, or crafting, this versatile tape provides reliable performance and ease of use. With its durability and effectiveness, this tape is an excellent choice for both personal and business needs, ensuring that your packages remain intact during handling and transit.

### PHYSICAL PROPERTIES

Item	Standard	Unit	Tolerance	Test Method
PP Thickness	28	mic	+/-10%	ASTM D3652
Weight of Glue	22	mic	+/-10%	ASTM D3652
Tensile Strength	110	N/25 mm	min	ASTM 3759
Elongation at Break	150	%	+/-10%	ASTM 3759
Shear Value	≥2	hour	min	ASTM D3654
Peel Adhesion on Steel	≥6	N/25 mm	+/-10%	ASTM 3330
Ball Tack (14#)	≤2.5	cm	max	ASTM D3330

Above figure is tested under room 23°C (+/-2°C) and humidity 55% (+/- 5%)

### STANDARD WIDTHS

48 mm

### STANDARD LENGTHS

100 m, 1828 m

### RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.