

ZEROTAPE® 400 PACKAGING TAPE



NOMINAL VALUES

Backing

Biaxially Oriented Polypropylene (BOPP)

Adhesive

XHT-90 | Extra High Tack

Tensile Strength MD TM 5004 by Afera

130 ± 30 (N/mm²)

Elongation at Break MD TM 5004 by Afera

130 ± 30 (%)

Adhesion to Steel TM 5001 by Afera

5.5 ± 1 (N/25mm)

Shear to Steel TM 5012 by Afera

Over 170 (h, 25mm x 25mm on stainless steel, 23°C)

Rolling Ball Task PSTC-6 (PSTC)

Under 3 (cm)

Film thickness

23 ± 1 (mic)

Total thickness

43µ (±6%)

DESCRIPTION:

Carrier BOPP 20 mic film with XHT-90 adhesive for manual carton sealing packaging applications.

APPLICATIONS:

- Manual carton sealing.
- Particularly suitable for light – weight non – critical packaging applications.

PROPERTIES:

- Environmentally friendly and ecological adhesive.
- Moisture compatible after application.
- UV resistant adhesive.
- Resistance to temperature changes.

The following data are nominal values based on PSTC, Afera and other standard tests. Information herein is only for general guidance and does not guarantee for accuracy and completeness. The user must, by test or otherwise, determine suitability for this product. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, is limited to the amount of product. We reserve the right to make changes without notice or obligation in our products and publications.