

TECHNICAL DATA SHEET

G-3122

ISSUE DATE: 06/11/2010

PRODUCT DESCRIPTION	G-3122 is a medium viscosity synthetic water based adhesive specially designed for high speed case and carton packaging application.	
USES	Glue lap, carton sealing.	
FEATURES	<ul style="list-style-type: none">• Excellent wet tack• Fast bond set up properties• Superior machining characteristics (wheel, roller or extrusion)• Bonds difficult to bond substrates	
TECHNICAL PROPERTIES	Viscosity:	1,600 - 2,200 cPs (#4/20rpm/25°C)
	pH:	4.0 - 6.0
	Specific Gravity:	1.07
	% of Solids:	56 ± 2%
PRODUCT APPLICATION	Recommended for wheel, roller or extrusion applicators	
ADDITIONAL DATA	N/A	
PACK SIZES	220 kg drum	1,100 kg tote
	20,000 kg tanker	weights may vary
STORAGE CONDITIONS	Keep from freezing. Avoid direct sunlight or heat.	
LIMITATIONS	Shelf Life: Six (6) months in the original unopened container when stored in a cool, dry area.	

Any recommendations contained herein or any information given by any Dural representative is based on tests and information believed to be accurate. However, since we have no control over the conditions under which our products are transported, stored, handled, or used by purchasers, all recommendations and sales are made on condition that Dural will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. It is the user's responsibility to ensure that this sheet is current prior to using the product.