

### DESCRIPTION:

Double sided tape, with polyester backing and acrylic adhesive for strong bonds on a variety of surfaces, such as paper and cardboard, including various LSE surfaces. Very flexible and conformable to irregular surfaces.

Used for flying splices in different industrial processes, with manual or automatic application.



\*Product presentation may be different than picture.

### SPECIALLY DESIGNED FOR:



PAPER AND  
CARDBORAD



SPLICING



IRREGULAR  
SURFACES

### PRODUCT ATTRIBUTES

Thickness mils(mm)	Adhesion to steel oz/in	Tensile Strength lb/in (kg/cm)	Elongation (%)	TEMPERATURE °F (°C)
<b>6.2 (0.16)</b>	<b>102</b>	<b>16.8 (3.0)</b>	<b>125</b>	<b>356 (180)</b>

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

### CONSTRUCTION:

STANDARD LENGTH (mm x m)	BACKING	COLOR	ADHESIVE:
 102 x 33 48 x 50 JUMBO	 PET FILM	 BLACK	 ACRYLIC

### Guarantee:

Hystik guarantees its tapes to be free from defects in materials and workmanship. This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices. It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.