



Technical Data Sheet

3M™ Double Coated Urethane Foam Tape 4026

Product Description

3M™ Double Coated Urethane Foam Tapes are conformable foams that offer high shear strength with a high temperature holding acrylic adhesive system for bonding to various types of surfaces for mounting, joining and holding.

Product Features

- The natural colored urethane foam tape products vary in color from white to light yellow. The color will change to light yellow upon exposure to sunlight (ultraviolet radiation). This color change is normal and does not affect tape performance.
- 3M™Double Coated Urethane Foam Tape 4026 is available in roll form and diecut pieces. Die-cut pieces of 3M tape 4026 is available in 3/4" or 1" squares, either individual pieces double lined with an extended liner on one side or in pads of 48 squares.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values	Additional Information
Adhesive Type	100	
Adhesive Carrier	Polyurethane Foam	
Liner Thickness	0.08 mm	
Color	Natural	
Liner Color	Green Plaid	View 
Test Name: Primary		
Thickness: Nominal	1.6 mm	
Thickness Tolerance	1.142 to 2.03 mm	

Thickness: Nominal	62.5 mil
Thickness Tolerance	45 to 80 mil
Foam Density	290 kg/m³
Foam Density	18 lb/ft³
Liner Thickness	3 mil

Typical Performance Characteristics

Property	Values	Additional Information
Normal Tensile	275 kPa	View 

Notes: (“T” Block); 1 in² (6.45 cm²); Jaw Speed 2 in/min (50 mm/min)

Normal Tensile	40 lb/in²	View 
Notes: (“T” Block); 1 in² (6.45 cm²); Jaw Speed 2 in/min (50 mm/min)		

Tensile Strength	1240 kPa
------------------	----------

Tensile Strength	180 lb/in²
------------------	------------

Elongation at Break	100 %
---------------------	-------

Short Term Temperature Resistance	380 °F
-----------------------------------	--------

Short Term Temperature Resistance	193 °C
-----------------------------------	--------

Long Term Temperature Resistance	104 °C
----------------------------------	--------

Long Term Temperature Resistance	220 °F
----------------------------------	--------

Static Shear	2000 g	
Static Shear	1000 g	
Static Shear	1000 g	
Static Shear	750 g	
Solvent Resistance	No apparent degradation when exposed to splash tests of most hydrocarbon solvents.	
UV Resistance	No apparent degradation when exposed to 7 days in U.V. chamber.	
Cold Flex	No cracking when flexed around a 1/4 in (6.4 mm mandrel).	View 
Temp C: -30C Temp F: -20F		

Available Sizes

Property	Values	Additional Information
Note	Subject to Minimum Order Requirements	
Standard Roll Length	32.9 m	
Standard Roll Length	36 yd	
Maximum Length	91 m	
Maximum Length	100 yd	
Available Width	1168 mm	
Available Width	46 in	

Normal Slitting Tolerance	±0.8 mm
---------------------------	---------

Normal Slitting Tolerance	±1/32 in
---------------------------	----------

Electrical and Thermal Properties

Property	Values	Additional Information
Dielectric Strength	8 to 12 V/μm	

Thermal Conductivity	0.062 W/m/K	
----------------------	-------------	--

Thermal Conductivity	0.036 (btu-in)/(h-ft²-°F)	
----------------------	---------------------------	--

Storage and Shelf Life

Store in original cartons at 70°F (21°C) and 50% relative humidity.
To obtain best performance, use these products within 24 months from date of manufacture.

Recognition/Certification

MSDS: 3M has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration’s Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the 3M directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards.

TSCA: These products are defined as articles under the Toxic Substances Control Act and therefore, are exempt from inventory listing requirements.

Bottom Matter

3M
Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550

Trademarks

3M is a trademark of 3M Company.

Automotive Disclaimer

Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer’s automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by the Technical Director of 3M’s Automotive Division. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer’s use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or

equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product.

NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

Handling/Application Information

Application Examples

The urethane foam tapes are generally ideal for interior applications or for exterior applications where the tape will be protected from the environment. The urethane foam is open cell.

3M™ Double Coated Urethane Foam Tape 4026 – Mount air fresheners and soap dispensers

Application Techniques

- Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure helps develop better adhesive contact and improve bond strength.
- To obtain optimum adhesion, the bonding surfaces must be clean, dry and well unified. Typical surface cleaning solvents are isopropyl alcohol* and water (rubbing alcohol) or heptane.
- Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

*Note: Be sure to follow the manufacturer’s precautions and directions for use when using solvents.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/p/d/b40067233/
Safety Data Sheet SDS	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=4026

Family Group

Link Tags:

- [• 4004](#)
- [• 4008](#)
- [• 4016](#)
- [• 4026](#)
- [• 4032](#)
- [• 4052](#)
- [• 4056](#)
- [• 4085](#)

Products	Adhesive Type	Adhesive Carrier	Liner Thickness	Color	Liner Color	Thickness: Nominal	Thickness Tolerance	Short Term Temperature Resistance	Long Term Temperature Resistance
4032	100	Polyurethane Foam	0.08 mm	Natural	Green Plaid	0.8 mm	0.64 to 1.02 mm	193 °C	220 °F
4008	100	Polyurethane Foam	0.08 mm	Natural	Green Plaid	3.2 mm	2.79 to 3.81 mm	193 °C	220 °F
4026	100	Polyurethane Foam	0.08 mm	Natural	Green Plaid	1.6 mm	1.142 to 2.03 mm	193 °C	220 °F
4085	740	Polyurethane Foam	0.08 mm	Natural	Tan	1.2 mm	1.00 to 1.45 mm	N/A	N/A
4004	100	Polyurethane Foam	0.08 mm	Natural	Green Plaid	6.4 mm	5.46 to 7.24 mm	193 °C	220 °F
4016	100	Polyurethane Foam	0.08 mm	Natural	Green Plaid	1.6 mm	1.142 to 2.03 mm	193 °C	220 °F

4052	100	Polyurethane Foam	0.08 mm	Black	Green Plaid	0.8 mm	0.64 to 1.02 mm	193 °C	220 °F
4056	100	Polyurethane Foam	0.08 mm	Black	Green Plaid	1.6 mm	1.142 to 2.03 mm	93 °C	125 °F

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M’s control and uniquely within user’s knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer’s application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M’s option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.